

## OSLO WATER DISCHARGE HOSE



<b>Application :</b>	Softwall lightweigh hose, used for industrial and waste waters which is specially suitable for submersible pumps, movable irrigation, systems, sewer cleaning, abrasion resistant.
<b>Tube :</b>	Black, smooth SBR
<b>Reinforcement :</b>	High strength synthetic cord
<b>Cover :</b>	Black, smooth (wrapped finish), EPDM, weather and ozone resistant
<b>Temperature :</b>	-40° - +100°C
<b>Branding :</b>	Green brand WATER – LOGO – OSLO 5 BAR Made in Italy – IVG 2000
<b>Manufacturer :</b>	IVG
<b>Remarks :</b>	According to ISO 1307/92 .

Code	Diameter mm	W.P./ B.P. bar	Weight kg/m	Coil m	VAT 0% EURO/m
<b>OSL038</b>	38x44	5/15	0,40	40	<b>11,90</b>
<b>OSL051</b>	51x57	5/15	0,53	40	<b>13,10</b>
<b>OSL063</b>	63x70	5/15	0,80	40	<b>17,10</b>
<b>OSL076</b>	76x81	5/15	0,78	40	<b>17,10</b>
<b>OSL102</b>	102x108	5/15	1,16	40	<b>23,40</b>
<b>OSL127</b>	127x133	5/15	1,45	30	<b>36,30</b>
<b>OSL152</b>	152x158	5/15	1,68	30	<b>45,10</b>
<b>OSL203</b>	203x211	5/15	2,47	20	<b>102,70</b>

## ROMA WATER DISCHARGE HOSE (RED)



<b>Application :</b>	Medium-duty water hose for industry, agriculture, mines, construction sites, street flushing etc.
<b>Tube :</b>	Black, smooth SBR
<b>Reinforcement :</b>	High strength synthetic cord
<b>Cover :</b>	Red, smooth (wrapped finis) SBR, abrasion, weather resistant
<b>Temperature :</b>	-35° - +70C
<b>Branding :</b>	Green brand - IVG
<b>Manufacturer :</b>	IVG

Code	Diameter mm	W.P. B.P. bar	Weight kg/m	Coil m	VAT 0% EURO/m
<b>ROO032</b>	32x42	6/18	0,80	40	<b>13,95</b>
<b>ROO051</b>	51x61	6/18	1,22	40	<b>20,80</b>
<b>ROO055</b>	55x66	6/18	1,47	40	<b>29,30</b>
<b>ROO090</b>	90x104	6/18	2,94	30	<b>54,40</b>
<b>ROO114</b>	114x130	6/18	4,28	30	<b>78,85</b>
<b>ROO127</b>	127x142	6/18	4,52	30	<b>97,10</b>