

## KANAL SEWER PIPE OPENING – AND FLUSHING HOSE



<b>Application :</b>	Hose designed for sewer pipe opening and flushing
<b>Tube :</b>	Black SBR
<b>Reinforcement :</b>	2 x high strength synthetic cord
<b>Cover :</b>	Black EPDM
<b>Temperature :</b>	- 20° - + 80°C
<b>Branding :</b>	"WG-KAN-25-200 bar- manufacturing date" + ring every 5 metres
<b>Manufacturer :</b>	HUTCHINSON
<b>Remarks :</b>	The hose is fixed length of 120 metres with the installed squeezed female/male couplings and with the manufacturer certificate. The max. manufacturing length 240 m. The hose is tested by the manufacturer in 250 bar test pressure for 5 min. On request also size 32 mm, with working pressure of 150 bar and bursting pressure of 300 bar.

Code	Diameter mm	W.P. B.P bar	Bend. radius mm	Weight kg/m	Coil m	VAT 0% EURO/m
KANAL019	19x32	200/500	150	0,65	120	28,50
KANAL025	25x39	200/500	150	0,85	120	37,80

## SAHARA LL 180°C HOT AIR HOSE



<b>Application :</b>	Flexible hose designed for delivery of hot air from compressor to tank truck.
<b>Tube :</b>	White, smooth, hot air resistant EPR
<b>Reinforcement :</b>	High strength synthetic cord, helix wire
<b>Cover :</b>	Blue, smooth (wrapped finish), abrasion and weather resistant EPDM
<b>Temperature :</b>	-40° - +180°C
<b>Branding :</b>	Red brand - IVG
<b>Manufacturer :</b>	IVG
<b>Remarks :</b>	The tube according to FDA

Code	Diameter mm	W.P. B.P. bar	Bend. radius mm	Weight kg/m	Coil m	VAT 0% EURO/m
SAH076	76x89	10/30	270	2,74	40	86,80